



- NOTES:
1. 4-STAGE REVERSE OSMOSIS SYSTEM WITH 100 GALLON PER DAY OUTPUT. STAGED FILTRATION INCLUDES 5.0 MICRON PREFILTER, GAC, 1.0 MICRON POST FILTER AND R.O. MEMBRANE T.F.C.
 2. 14 GALLON BLADDER TANK WITH 8 GALLON DRAW DOWN CAPACITY AT 40 PSI.
 3. 3/8" TUBE INLET FOR R.O. PRETREATMENT.
 4. GEMINI HP LOOP - 3/8" TUBE INLET. 3/8" PORT DISPENSE OULTET.
 5. (2) LOW TOC MIXED BED CARTRIDGES AND 0.2 MICRON FILTER INCLUDED.
 6. GEMINI HP LOOP IS 110 VAC/60 HZ

THIS DRAWING CONTAINS PROPRIETARY INFORMATION. ANY USE OF THIS DRAWING OR INFORMATION CONTAINED HEREIN FOR OTHER THAN THE PURPOSE FOR WITH THIS DRAWING IS FURNISHED IS FORBIDDEN.

CUSTOMER:

LOCATION:

ARIES FILTERWORKS WEST BERLIN, NJ (856) 768-9600			
TITLE REVERSE OSMOSIS SYSTEM WITH STORAGE AND DEIONIZATION POLISHING			
SIZE	DWN: JJB	DWG NO.	REV
	APVD:	031705-PID	
SCALE NONE	DATE 17 MAR 05	SHEET 1 OF 1	